



MADS-K

Modular Anti-Drone System Kit

The MADS-K (Modular Anti-Drone System Kit) is a modular, low-cost, lightweight, simultaneous ground target and UAS detection and mitigation system. MADS-K provides the operator a stand-alone mission-scalable C-UAS capability.

Easy to train, deploy, operate and maintain, the MADS-K baseline system's modular design incorporates a radar, EO/IR camera, and jammer operating in 360° of azimuth and positive target identification at tactically significant ranges. MADS-K detects, positively identifies, tracks, and when desired jams UAS group 1 and 2 targets.

MISSIONS

Counter UAS

Ground Target Detection & Mitigation

Homeland Security

Force Protection



Optional modular designs include multiple C2 integrations, hard-kill and soft-kill, and On the Move (OTM) capabilities.

FEATURES

MARS-K V1 RADAR

Air/Ground Surveillance Mode Optimized for C-UAS

- 360 degree coverage
- Detects UAVs (rotary and fixed wing), ultralights, aircraft, dismounted personnel and ground vehicles from close range to 9.3 miles out (250 m out to 15 km)
- Scan rate as low as 2 seconds
- Detects up to 100 simultaneous targets (ground and air)

Detection Ranges

- Detects, tracks and positively classifies targets from close range to 9.3 miles (250 m out to 15 km), target dependent. S-800 sized target 1.8 miles (3 km) / DJI Phantom size targeted 1.2 miles (2 km)

Environmental

- Operating temperature: -32°C to + 50°C
- Non-operating temperature: -33°C to + 71°C

Mechanical and Electrical

- Weight: 55 lbs
- Power: 12 VDC, 24 VDC, 110-220 VAC, 185 W
- 6 BA2590 batteries provide 10 hours of operation (additional batteries increase hours of operation)

MINI-POP ELECTRO-OPTICAL/ INFRARED (EO/IR) CAMERA

- Thermal imaging camera and CCD
- Optical-Tracking
- Video Motion Detection (VMD) capability
- Day camera: 768x480 for NTSC, 752x576 for PAL, 1.6° to 40° FOV
- IR camera: 640x480, 2° to 25° FOV
- Coverage: 360° azimuth/120° in elevation (+90° to -30°)
- Weight: 20.4 lbs
- Size: 13" high, 8" diameter

Ranges:

- Cessna-sized target detection approx. 3.7 miles (6 km) / recognition approx 2 miles (3 km)
- S-800- sized target detection approx. 1.2 miles (2 km) / recognition approx. 1 mile (1.3 km)
- DJI Phantom-sized target detection approx. 1 mile (1.4 km) / recognition 1/2 mile (700 m)

ELK-7012D DIRECTIONAL JAMMER

- Jams a variety of communications within ISM, U-NII, and GNSS
- Range: up to 1 mile (1.5 km)
- Weight: 44 lbs
- Size: 50" L x40" W x40" H
- Peak Power: 300W

Frequency Bands

- Select frequencies within ISM bands from 400MHz to 6GHz
- Beamwidth: 40° to 80°; frequency dependent

The information contained within this product data sheet is not subject to export controls and may be released without export restrictions. The equipment described herein may require U.S. Government authorization for export purposes. Diversion contrary to U.S. law is prohibited.

ELTA North America
8955 Henkels Lane
Annapolis Junction, MD 20701
eltanorthamerica.com

Where Courage Meets Technology™